

OFFICE OF THE DIVISIONAL MANAGER, CTU & DIRECTOR TRANSPORT,  
U T, CHANDIGARH.  
(Plot No. 701, Industrial Area, Phase I Chandigarh)

QUOTATION NOTICE

Ref. No. BA/HO/CTU/2021/ 2374

Dated: 19/3/21

Chandigarh Transport Undertaking, Chandigarh invites quotations in sealed cover from the firm/companies/Civil contractor for renovation/repair of Room and fabricating counters to be created for making seating arrangements of at-least 04-05 officials in the aforesaid room adjacent to the Railway Reservation Counter at First floor of Inter State Bus Terminus, Sector-17 which has been identified for opening of Cash Branch & Box Branch.

The offer/price bid form and detail terms and condition of the quotation can be downloaded from the website of CTU Chandigarh or can also be obtained from the office of the undersigned as free of cost. The detail of items to be executed along with approximate quantity is as under:-

Sr. No.	Nomenclature	Size Specification	Qty required
	As per annexure-'A'		

Note:- The quantity of the material can be increased/decreased as per demand/actual consumption of the department.

For this purpose, the Quotations are invited from the firm/companies/Civil contractor (who is capable) for renovation/repair of Room and fabricating counters to be created for making seating arrangements of at-least 04-05 officials in the aforesaid room. The firm/companies/Civil contractor are required to quote their rates including all taxes/duties/GST (Landed Rate) on the prescribed Performa enclosed with this notice.

The quotations in sealed cover super scribed in bold letters "**QUOTATION FOR RENOVATION/REPAIR OF ROOM AND FABRICATING COUNTERS ADJACENT TO THE RAILWAY RESERVATION COUNTER AT FIRST FLOOR OF INTER STATE BUS TERMINUS, SECTOR-17**" should be sent in the office of Divisional Manager, CTU & Director Transport, UT, Plot No. 701, Industrial Area, Phase I, Chandigarh by hand/Registered post so as to reach on or before Chandigarh on or before **26<sup>th</sup> March, 2021 upto 2.00 PM.** The said quotations will be opened in the presence of the representatives of the firm/companies/Civil contractor whosoever wishes to be present on the **same day at 3.30 P.M.**

Quotations received late from the stipulated date and time shall not be considered and shall be rejected out rightly.

The undersigned reserves every right to (a) cancel / withdraw / amend the advertisement or extend the due date at his sole discretion or (b) accept or reject any quotation without assigning any reason.

  
Assistant Controller (F&A)  
For Divisional Manager, CTU &  
Director Transport, U.T.,  
Chandigarh 

**TERMS AND CONDITIONS FOR RENOVATION/REPAIR OF ROOM AND FABRICATING COUNTERS TO BE CREATED FOR MAKING SEATING ARRANGEMENTS OF AT-LEAST 04-05 OFFICIALS IN THE AFORESAID ROOM ADJACENT TO THE RAILWAY RESERVATION COUNTER AT FIRST FLOOR OF INTER STATE BUS TERMINUS, SECTOR-17**

1. The rates quoted should be F.O.R. destination i.e. at ISBT-17 Chandigarh including all Taxes, installation & commissioning etc.
2. The quotation shall be valid for two months from the date of issue of rate acceptance letter.
3. Standard material of same will only be accepted as approved by the Inspection Committee constituted for the purpose and as installed in Depot No-II Cash branch & Box Branch and as per CPWD schedule.
4. Incomplete/conditional quotations will not be entertained.
5. The payment will be made through bank draft/RTGS only after submission of bill by the contractor/successful bidder and after verification by the CTU committee.
6. Payment will be made within 10-15 days from the date of completion of work.
7. Any conditional terms and conditions mentioned by the firm in their covering letter or in the bid documents quotation will not be considered.

  
Assistant Controller (F&A)  
For Divisional Manager, CTU &  
Director Transport, U.T.,  
Chandigarh 



## OFFER / PRICE BID

I, the undersigned \_\_\_\_\_ S/o Shri \_\_\_\_\_ on behalf of M/s. \_\_\_\_\_ of which I am a partner /proprietor/Director/Manager/ Partner \_\_\_\_\_ (please tick mark) hereby submit my offer as under: -

1. I am duly authorized to submit this Offer/Price Bid.
2. I have read all the Terms and Conditions etc., in detail and on the basis of my full study of the above mentioned terms and conditions and the Quotation Notice, I undertake to supply /carry out the works in accordance with the bill of quantity mentioned at annexure-A
3. I undertake that I/my firm/company have not been blacklisted by the Department of Govt. of India or any State Govt. or any Union Territory or any Public undertaking.

Signature of the Bidder \_\_\_\_\_  
Name of the Bidder \_\_\_\_\_  
(With Rubber Stamp)  
Address \_\_\_\_\_  
Mobile No. \_\_\_\_\_  
Tel No. \_\_\_\_\_  
PAN/TAN NO. \_\_\_\_\_  
GST No. \_\_\_\_\_  
E-Mail ID \_\_\_\_\_

NOTE:-

1. The bid should be unconditional. Conditional bids shall be out-rightly rejected.
2. There should not be any cutting or overwriting in the Offer/Price Bid form. Photo copy/typed form can also be used in case of damage or cuttings etc.
3. In case of difference in the bid amount expressed in figures and words, the amount expressed in words will

11  
ANNEXURE - A

DETAILED ESTIMATE FOR THE RENOVATION OF THE FIRST FLOOR OF THE CANTEEN BLOCK FOR BOX BRANCH AND CASH BRANCH AT CTU DEPOT NO.II, INDUSTRIAL AREA PHASE-I, CHANDIGARH.

Sr. No.	DSR No.	Description	Qty	Unit	Rate	Amount
1	15.2	Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer -in - charge...				
	15.2.1	Nominal concrete 1:3:6 or richer mix ((c equivalent design mix)	1.46	Cum		
2	15.2	Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer -in - charge...				
	15.2.2	Nominal concrete 1:4:8 or leaner mix ((c equivalent design mix)	3.66	Cum		
3	15.13	Dismantling doors, windows and clerestory windows (steel or wood) shutter including chowkhats, architrave, holdfasts etc. complete and stacking within 50 metres lead :				
	15.13.1	Of area 3 sq. metres and below	1.00	Each		
4	4.2	Providing and laying cement concrete in retaining walls, return walls, walls (any thickness) including attached pilasters, columns, piers, abutments, pillars, posts, struts, buttresses, string or lacing courses, parapets, coping, bed blocks, anchor blocks, plain window sills, filllets, sunken floor etc., up to floor five level, excluding the cost of centering,shuttering and finishing:				
	4.2.8	1:5:10 (1 cement : 5 coarse sand (zone-III) : 10 graded stone aggregate 40 mm nominal size)	2.74	Cum		
5	4.2	Providing and laying cement concrete in retaining walls, return walls, walls (any thickness) including attached pilasters, columns, piers, abutments, pillars, posts, struts, buttresses, string or lacing courses, parapets, coping, bed blocks, anchor blocks, plain window sills, filllets, sunken floor etc., up to floor five level, excluding the cost of centering,shuttering and finishing:				
	4.2.3	1:2:4 (1 Cement : 2 coarse sand (zone-II) : 4 graded stone aggregate 20 mm nominal size)	1.46	Cum		
6	5.3	Reinforced cement concrete work in beams, suspended floors, roofs having slope up to 15° landings, balconies, shelves, chajjas, lintels, bands, plain window sills, staircases and spiral stair cases above plinth level up to floor five level, excluding the cost of centering, shuttering, finishing and reinforcement with 1:1.5:3 (1 cement : 1.5 coarse sand(zone-II) : 3 graded stone aggregate 20 mm nominal size).	0.14	Cum		
7	5.9	Centering and shuttering including strutting, propping etc. and removal of form for :	2.27	Sqm		
	5.9.4	Shelves (Cast in situ)				
8	5.22A	Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete above plinth level.	32.19	Kg		
	5.22A.6	Thermo-Mechanically Treated bars of grade Fe-500D or more				
9	6.13	Half brick masonry with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level.	8.33	Sqm		
	6.13.2	Cement mortar 1:4 (1 cement :4 coarse sand)				
10	8.2	Providing and fixing 16 to18 mm thick gang saw cut, mirror polished, pre-moulded and prepolished, machine cut for kitchen platforms, vanity counters, window sills, fascias and similar locations of required size, approved shade, colour and texture laid over 20 mm thick base cement mortar 1:4 (1 cement : 4 coarse sand), joints treated with white cement, mixed with matching pigment, epoxy touch ups, including rubbing, curing, moulding and polishing to edges to give high gloss finish etc. complete at all levels.				
	8.2.2	Granite of any colour and shade				
	8.2.2.2	Area of slab over 0.50 sqm	10.32	Sqm		
11	9.21	Providing and fixing ISI marked flush door shutters conforming to IS : 2202 (Part I) non-decorative type, core of block board construction with frame of 1st class hard wood and well matched commercial 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters:				
	9.21.1	35 mm thick including ISI marked Stainless Steel butt hinges with necessary screws	1.88	Sqm		
12	9.83	Providing and fixing aluminum die cast body tubular type universal hydraulic door closer (having brand logo with ISI, IS : 3564, embossed on the body, door weight upto 35 kg and door width upto 700 mm), with necessary accessories and screws etc. complete.	7.00	Each		



13	9.96	Providing and fixing aluminium sliding door bolts. ISI marked anodised (anodic coating not less than grade AC 10 as per IS : 1868), transparent or dyed to required colour or shade, with nuts and screws etc. complete.	1.00	Each		
	9.96.1	300x16 mm				
14	9.97	Providing and fixing aluminium lower bolts. ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete.	1.00	Each		
	9.97.1	300x10 mm				
15	9.100	Providing and fixing aluminium handles. ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete.	2.00	Each		
	9.100.1	125 mm				
16	9.101	Providing and fixing aluminium hanging floor door stopper. ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour and shade, with necessary screws etc. complete.	2.00	Each		
	9.101.2	Twin rubber stopper				
17	10.14	Providing and fixing pressed steel door frames conforming to IS-4351, manufactured from commercial mild steel sheet of 1.60 mm thickness, including hinges, jamb, lock jamb, bead and if required angle threshold of mild steel angle of section 50x25 mm, or base ties of 1.60 mm, pressed mild steel welded or rigidly fixed together by mechanical means, including M.S. pressed butt hinges 2.5 mm thick with mortar guards, lock strike-plate and shock absorbers as specified and applying a coat of approved steel primer after pre-treatment of the surface as directed by Engineer-in-charge.				
	10.14.1	Profile B				
	10.14.1.1	Fixing with adjustable lugs with split end tail to each jamb	6.20	Rmtl		
18	NS	Providing and laying full body anti skid vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS : 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joints with white cement and matching pigments etc. complete.	36.59	Sqmm		
		Size of Tile 600x600 mm				
19	NS	Providing and laying full body anti skid vitrified tiles in different sizes (thickness to be specified by manufacturer), with water absorption less than 0.08% and conforming to IS : 15622, of approved make, in all colours & shade, in skirting, riser of steps, over 12 mm thick bed of cement mortar 1:3 (1 cement: 3 coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joint with white cement & matching pigment etc. complete.				
		Size of Tile 600x600 mm	2.99	Sqmm		
20	NS	Providing and fixing false ceiling at all height including providing and fixing of frame work made of special sections, power pressed from M.S. sheets and galvanized with zinc coating of 120 gms/sqm (both side inclusive) as per IS : 277 and consisting of angle cleats of size 25 mm wide x 1.6 mm thick with flanges of 27 mm and 37mm, at 1200 mm centre to centre, one flange fixed to the ceiling with dash fastener 12.5 mm dia x 50mm long with 6mm dia bolts, other flange of cleat fixed to the angle hangers of 25x10x0.50 mm of required length with nuts & bolts of required size and other end of angle hanger fixed with intermediate G.I. channels 45x15x0.9 mm running at the spacing of 1200 mm centre to centre, to which the ceiling section 0.5 mm thick bottom wedge of 80 mm with tapered flanges of 26 mm each having lips of 10.5 mm, at 450 mm centre to centre, shall be fixed in a direction perpendicular to G.I. intermediate channel with connecting clips made out of 2.64 mm dia x 230 mm long G.I. wire at every junction, including fixing perimeter channels 0.5 mm thick 27 mm high having flanges of 20 mm and 30 mm long, the perimeter of ceiling fixed to wall/partition with the help of rawl plugs at 450 mm centre, with 25mm long dry wall screws @ 230 mm interval, including fixing of gypsum board to ceiling section and perimeter channel with the help of dry wall screws of size 3.5 x 25 mm at 230 mm c/c, including jointing and finishing to a flush finish of tapered and square edges of the board with recommended jointing compound, jointing tapes, finishing with jointing compound in 3 layers covering upto 150 mm on both sides of joint and two coats of primer suitable for board, all as per manufacturer's specification and also including the cost of making openings for light fittings, grills, diffusers, cutouts made with frame of perimeter channels suitably fixed, all complete as per drawings, specification and direction of the Engineer in Charge but excluding the cost of painting with :				

✕



21	NS	12.5 mm. thick tapered edge gypsum plain board conforming to IS: 2095- (Part I) : 2011 (Board with BIS certification marks)	39.05	Sqm		
		Providing and fixing of 100 mm vertical blinds made from polyester/fiber glass coated (i.e. as per site requirements) having head rail of extruded alloy section is powder coated for smooth paint finish and corrosion resistance of size 50mm wide, 25mm high, thickness 1.25mm. Control unit from high strength plastic with in build reduction gear box of planetary lift gear hub for the turning of louvers of 180 degree. The runners made of moulded plastic having tounge polycon stem to hold louvers and to provide frictionless rotation of louvers. The cord is 2.2mm in diameter, braided high strength polyester fiber and bottom weight of powder coated galvanized steel sheet 1.8mm thick to add weight to louvers and keeps it straight complete in all respects to satisfaction of Engineer in charge.	12.20	Sqm		
22	13.4	12 mm cement plaster.				
	13.4.1	1.4 (1 cement : 4 coarse sand)				
23	9.105	Providing and fixing partition upto ceiling height consisting of G.I. frame and required board, including providing and fixing of frame work made of special section power pressed/ roll form G.I. sheet with zinc coating of 120 gms./sqm(both side inclusive), consisting of floor and ceiling channel 50mm wide having equal flanges of 32 mm and 0.50 mm thick, fixed to the floor and ceiling at the spacing of 610 mm centre to centre with dash fastener of 12.5 mm dia meter 50 mm length or suitable anchor fastener or metal screws with nylon plugs and the studs 48 mm wide having one flange of 34 mm and other flange 36 mm and 0.50 mm thick fixed vertically within flanges of floor and ceiling channel and placed at a spacing of 610 mm centre to centre by 6 mm dia bolts and nuts, including fixing of studs along both ends of partition fixed flush to wall with suitable anchor fastener or metal screws with nylon plugs at spacing of 450 mm centre to centre, and fixing of boards to both side of frame work by 25 mm long dry wall screws on studs, floor and ceiling channels at the spacing of 300 mm centre to centre. The boards are to be fixed to the frame work with joints staggered to avoid through cracks. Galvanized M.S. fixing channel of 99 mm width (0.9 mm thick of two boards, fixed to the studs using metal to metal flat head screws, including jointing and finishing to a flush finish with recommended jointing compound, jointing tape, angle beads at corners (25 mm x 25 mm x 0.5 mm), joint finisher and two coats of primer suitable for board as per manufacturer's specification and direction of engineer in charge all complete.	8.85	Sqm		
24	11.48	Grouting the joints of flooring tiles having joints of 3 mm width, using epoxy grout mix of 0.70 kg of organic coated filler of desired shade (0.10 kg of hardener and 0.20 kg of resin per kg), including filling / grouting and finishing complete as per direction of Engineer-in-charge.				
	11.48.2	Size of Tile 600x600 mm				
25	11.50	Deduct for not grouting the joints with white cement and matching pigment in the items of fixing of vitrified tiles	39.58	Sqm		
26	21.1	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle. Aluminium snap heading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately).	39.58	Sqm		
	21.1.1	For fixed portion				
	21.1.1.2	Powder coated aluminium (minimum thickness of powder coating 50 micron)	73.00	Kg		
27	NS	Supply & installation of Dorma Frameless Glass Door of make with overpanel / sidelight using 12mm thick toughened glass of Saint Gobain / or approved equivalent with Dormakaba Crown series make die cast patch fitting with stainless steel cover PT 40 , PT 10, PT 20, PT 24, US-10. Dorma pull Handle TGD-H 450 back to back with 350mm CTC, adjustable fixing for glass Length =450mm, 25mm dia, -SS304 Finish. mill. Dorma floor spring BTS 75V with std. spindle and cover plate. As per DIN EN 1154 (500,000 cycle tested) . Finish: Satin stainless steel Dorma floor stop half dome with 45mm dia with fixing accessories, in satin Chrome. Final certifications of products should be submitted be from the product manufacturer for the originality of the product and manufacturer should have its own service team . The above work complete in all respect as per approved drawings and to the satisfaction of Engineer-in-Charge.	1.88	Sqm		



28	NS	Providing and fixing 8 mm toughened glass glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge. (Cost of aluminium snap beading shall be paid in basic item).	6.64	Sqm		
29	NS	Providing and fixing wooden cupboard made up of 19 mm commercial block board (SI) Marked having hollow wood frame of size 2.5'x1.5'. Making box of size 8'-0"x6'-9" including back panel. The cupboard consist of 6 cabins size 4'-0"x2'-3". The cupboard consist of shutter system of size 2'-0"x6'-9" of single shutter. The cupboard have 4 No. inner shelves in center. All the internal surface are finished with white paint. Two or more coat over an under coat of primer of approved brand and manufacture. All the exposed surface is finished with approved shade 1.00 mm laminate sheet. The rate further includes the cost of leak wood lipping 19 mm, piano type hinges 19mm, aluminium handles 75 mm, Magnet Catcher, knobs, screws, cupboard Locks, nails, Synthetic adhesive spirit polishing on lipping complete in all respect and to the entire satisfaction of Engineer in charge.	5.65	Sqm		
30	15.60	Disposal of building rubbish / malba / similar unserviceable, dismantled or waste materials by mechanical means, including loading, transporting, unloading to approved municipal dumping ground or as approved by Engineer-in-charge, beyond 50 m initial lead, for all leads including all lifts involved.	5.12	cum		
Total						

*(Handwritten mark)*